



NeoSapphire

NS3405 All-Flash Array

- Superior performance with 360K IOPS in a compact 1U form factor
- Easy maintenance with 10 hot-swappable SSDs and 2 PSUs
- Fault tolerance with automatic data reconstruction for a peace of mind




FlexiRemap®
NeoSapphire 3405 All-Flash Array
SPECIFICATIONS

Form Factor	1U rack mount
IOPS for 4KB Random Writes ¹	360K sustained
Flash Management	FlexiRemap technology
Usable Capacity ²	5TB
Number of SSDs	10
SSD Type	SATA
Flash Type	MLC
Connectivity	4 x 10GbE SFP+
Storage Protocol	iSCSI NFS, CIFS/SMB
Management Interface	Web-GUI (via HTTP/HTTPS) CLI (via serial port)
Power Supply	700W/750W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • High performance in compact form factor • Data protection through redundancy
Software Function	<ul style="list-style-type: none"> • Free Clone • Snapshot • Snapshot Backup/Recovery • Remote Replication • Thin Provisioning • Thick Provisioning • Inline Deduplication • vSphere Web Client Plug-in
Certification	<ul style="list-style-type: none"> • VMware Ready
Dimensions (W x D x H)	437mm x 597mm x 43mm (17.2in x 23.5in x 1.7in)
Net Weight ³	12.7kg (28.0lb)
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ Based on designated testing conditions. Performance may vary with different applications or product configurations.

² Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

³ Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.

VC20170628