



NeoSapphire H710

- Scale-up capacity and uncompromised performance for 600K IOPS for 4KB random write
- High availability via shared-nothing architecture with symmetric active-active nodes
- A flexible choice from 27TB to 221TB usable capacity
- Built for data center, cloud computing, HPC, AI, virtualization, OLTP and data mining



FlexiRemap®

NeoSapphire All-Flash Array



NeoSapphire H710 All-Flash Array and Expansion Enclosure SPECIFICATIONS

	NeoSapphire H710	NeoSapphire J212	NeoSapphire J214
Form Factor	4U rack mount	2U rack mount	4U rack mount
Expansion Enclosure	J212 or J214	---	---
IOPS for 4KB Random Writes ¹	600K sustained	---	---
Flash Management	FlexiRemap [®] technology	---	---
Usable Capacity ²	27TB w/ Expansion Max. 221TB	Max. 110TB	Max. 165TB
Number of SSDs	48 drives w/ J212 Expansion Max. 144 drives w/ J214 Expansion Max. 336 drives	24	72
SSD Type	SATA	SATA	SATA
Flash Type	MLC or TLC	MLC or TLC	MLC or TLC
Connectivity	16 x 10GbE SFP+ Or 8 x 16G Fibre Channel LC SFP+	2 x 12G SAS ports (8 lanes per port)	2 x 12G SAS ports (8 lanes per port)
Storage Protocol	iSCSI or Fibre Channel	---	---
Management Interface	Web GUI (via HTTP/HTTPS) CLI (via serial port or SSH)	---	---
Power Supply	920W 1+1 redundant (per node) Or 920W+BBP (per node)	740W 1+1 redundant	1000W/1200W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • High Availability via shared-nothing architecture with symmetric Active-Active nodes • 100% no single point of failure • Scale-up capability • Efficient FlexiDedupe[™] data reduction 	<ul style="list-style-type: none"> • 2U 24-bay space-saving high density model for storage capacity expansion • High speed 12Gb/s SAS expansion connectivity • Online capacity expansion technology 	<ul style="list-style-type: none"> • 4U 72-bay space-saving high density model for storage capacity expansion • High speed 12Gb/s SAS expansion connectivity • Online capacity expansion technology
Software Function	<ul style="list-style-type: none"> • Free Clone • Snapshot • Snapshot Backup/Recovery • Group Snapshot • Remote Replication • Thin Provisioning • Thick Provisioning • Inline Deduplication • Background Deduplication • vSphere Web Client Plug-in • SED 	---	---
Dimensions (W x D x H)	437mm x 630mm x 89mm (17.2in x 24.8in x 3.5in) (per node)	437mm x 630mm x 89mm (17.2in x 24.8in x 3.5in) (per node)	437mm x 699mm x 178mm (17.2in x 27.5in x 7in) (per node)
Net Weight ³	19.8kg (43.7lb) (per node)	26.39kg (58lb)	38.34kg(84lb)
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (Non-Operating): -20°C to 60°C (-4°F to 141°F)		
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing		

¹ Based on designated testing conditions. Performance may vary with different applications or product configurations.

² Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

³ Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions. VC20170815